## MARS14 Simulation of FØ Lambertson Heating

## N.V. Mokhov

Fermi National Accelerator Laboratory
P.O. Box 500, Batavia, Illinois 60510

June 4, 2003

Temperature rise in a bronze liner of the Tevatron FØ Lambertson at injection is calculated via express MARS14 [1] simulations. The beam parameters and Lambertson geometry were provided by Petr Ivanov and implemented into the model. A 150-GeV proton beam RMS spot sizes are  $\sigma_x$ =1.9 mm and  $\sigma_y$ =1.15 mm. Total proton beam is  $10^{13}$  ppp. The 0.4-mm thick liner is made of the Cu-Be bronze C17200 (Be 1.9%, Co 0.2%, Cu 97.9%,  $\rho$ =8.25 g/cm<sup>3</sup>). Effective horizontal distance from the beam center to the liner is  $3\sigma_x$ =5.7 mm. It follows from measurements that some fraction  $\eta$  of the proton beam is lost on the Lambertson over the first 100 turns. It means that one can estimate an instantaneous temperature rise  $\Delta T$  from calculated energy deposition distributions. A corresponding instantaneous temperature after such a fast "scraping" is calculated then as  $T = T_0 + \Delta T$ , where  $T_0 = 20^{\circ}C$ . We assumed two values for the number of protons lost on the Lambertson:  $\eta_1 = 5\%$  or  $5 \times 10^{11}$ , and  $\eta_2 = 1\%$  or  $10^{11}$ . Two conservative assumptions were made: a beam density distribution in the tail outside of the  $3\sigma$  envelope is Gaussian, and these "tail" protons hit normally the upstream face of the Lambertson's first module.

The calculations reveal that the maximum energy deposition – and temperature rise respectively – takes place in the liner in the horizontal plane at z  $\sim$  15 cm from the entrance to the first module. Fig. 1 shows calculated energy deposition isocontours at 10 < z < 20 cm. Longitudinal profiles of a maximum instantaneous temperature in the liner is shown in Fig. 2 for 5% and 1% of the beam hitting the Lambertson. One sees that even with rather conservative assumptions, the maximum temperatures do not exceed  $67^{\circ}C$  and  $29^{\circ}C$  in these two cases, respectively.

## References

[1] N.V. Mokhov, "The MARS Code System User's Guide", Fermilab-FN-628 (1995); N.V. Mokhov, O.E. Krivosheev, Proc. Monte Carlo 2000 Conf., p. 943, Lisbon, October 23-26, 2000; N.V. Mokhov, "Status of MARS Code", Fermilab-Conf-03/053 (2003); <a href="http://www-ap.fnal.gov/MARS/">http://www-ap.fnal.gov/MARS/</a>.




Figure 1: Energy deposition isocontours at shower maximum.




Figure 2: Longitudinal profiles of maximum instantaneous temperature in the liner.